

## Dragon medium stock fencing

APPLICATIONS > Agriculture | Rail | Highways | Pipeline

## **Product description**

Hinge joint field fence manufactured with 2Life® wire which lasts at least two times longer than heavily galvanised.

- Triple coating of zinc, aluminium and our green anti-corrosion barrier giving enhanced protection.
- A conventional hinge joint field fence manufactured to BS EN 10223-5. Designed for ease of pull up when erecting. Suitable for the permanent fencing of livestock – sheep, cattle, pigs etc.
- A centreless core to provide a snag free, easily rolled out fence where all of the roll can be used.
- A deep crimp between the verticals to aid tensioning over uneven ground, elasticity against livestock and different weather conditions and to allow rainwater to drain away from the joint.

## Coatings

> 2Life® lasts at least 2 times longer than heavily galvanised wire BS EN 10244-2 Class A

## Mesh

- Top & bottom wires Ø 3.00 mm. Min 600 N/mm<sup>2</sup>
- ➤ Horizontal wires Ø 2.50 mm. Min 600 N/mm²
- Vertical wires Ø 2.50 mm, Min 350 N/mm<sup>2</sup>

Characteristics					
Designation	Height	Vertical spacing	Length	Nominal weight	Number of rolls per pallet
	mm	mm	m	kg	4. 25/2/240
C8/80/15	800	150	50/100/250	32/64/160	20/12/4
Other patterns, sizes and heights available on request.					





ArcelorMittal Sheffield, Vulcan Works, Birley Vale Close, Sheffield S12 2DB Telephone: +44 (0) 114 239 2601

Fax: +44 (0) 114 264 2514



