


Integral 8




ArcelorMittal


8 outer strands parallel closed rope



8x19 SLR



8x26 WSR



8x31 WSR

	Diameter		Section mm ²	Mass kg/m	Min. breaking load kN	
	mm	inch				
8x19 SLR	2160 MPa					
	6,4	-	23,7	0,20	43	
	7	-	28,3	0,25	51	
	7,2	-	29,9	0,26	54	
	8	5,16	36,8	0,32	67	
	9	-	46,6	0,40	85	
	10	-	57,1	0,50	105	
	11	7/16	69,1	0,60	127	
	12	-	82,1	0,71	150	
	13	1/2	95,9	0,83	175	
	14	9/16	112,2	0,97	205	
	15	-	130,0	1,13	238	
	8x26 WSR	16	5/8	149,1	1,31	273
		18	-	187,4	1,64	343
		19	3/4	208,8	1,83	382
20		-	231,3	2,02	423	
22		7/8	279,9	2,45	512	
24		-	333,2	2,92	609	
25		-	361,5	3,16	661	
26		-	379,9	3,32	703	
28		1-1/8	454,0	3,96	821	
28,6		-	473,7	4,13	856	
8x31 WSR	30	-	521,2	4,55	942	
	32	1-1/4	602,8	5,29	1086	
	34	1-3/8	680,5	5,97	1226	
	36	-	762,9	6,69	1375	
	38	1-1/2	842,2	7,38	1495	
	40	-	943,3	8,27	1658	
	42	1-5/8	1040,0	9,12	1828	
	44,5	-	1117,1	9,74	2003	
	46	-	1193,7	10,41	2140	
	48	1-7/8	1296,6	11,35	2309	
	50	2	1406,9	12,32	2505	
	50,8	-	1452,3	12,71	2586	
52	-	1521,7	13,32	2710		

Indicative values – Tolerance on diameter: ArcelorMittal design (0; +4%)

Integral 8 must **never** be used with a swivel



Depending on applications, design can be specifically adapted. Please contact us for further information.