

Distribution Solutions
WireSolutions



ArcelorMittal

Carrelux[®] Annealed
Welded mesh in very low annealed wire





ArcelorMittal


Carrelux® Annealed

Welded mesh in very low annealed wire

Product description

Used in construction as the primary reinforcement for cementitious floor screeds

- ▶ Product complies with NF P61-202 (DTU 52.1)
- ▶ A professional product easy to carry, store and handle
- ▶ Large program with sizes up to 150 cm



Applications

- ▶ Construction
- ▶ Agriculture

Quality

- ▶ Annealed

Characteristics

Standard types

	Min. weight (m ²)	Mesh size (mm)	Wire Ø (mm)	Width (cm)	Roll length (m)	Surface (m ²)	Roll weight (kg)	Rolls/pallet
E	220	50 x 50	0.9	100	100	100	22	16
F	325	100 x 100	1.8 x 1.4	100	100	100	33	9
G	650	50 x 50	1.8 x 1.4	100	50	50	33	9

Specific types

	Min. weight (m ²)	Mesh size (mm)	Wire Ø (mm)	Width (cm)	Roll length (m)	Surface (m ²)	Roll weight (kg)	Rolls/pallet
E	220	50 x 50	0.9	120*	100	120	26.5	16
F	325	100 x 100	1.8 x 1.4	120*	100	120	39	9
G	650	50 x 50	1.8 x 1.4	120*	50	60	39	9
G	650	50 x 50	1.8 x 1.4	120*	50	75	49	9

ArcelorMittal Bissen & Bettembourg
Route de Finsterthal, L-7703 Bissen
T +352 835 772, F +352 835 698

www.arcelormittal.com/wiresolutions

