

Distribution Solutions
WireSolutions



ArcelorMittal

Scorpio[®]

Barbed wire with Crapal[®]2 coating





ArcelorMittal

Scorpio®

Barbed wire with Crapal®2 coating

Product description

Crapal®2 coating – Life span **2x longer** than EN 10244-2 heavily galvanised wire

- ▶ Manufactured with high tensile wire in Ø 1.70 mm, Scorpio® has a minimum breaking load of 440 kg (equivalent to a low carbon steel barbed wire with a diameter of 2.70 mm)
- ▶ Alternating twists lock the barbs at regular spacings of 10 cm preventing them from slipping
- ▶ Delivered in a protective cardboard with carrying handle
- ▶ Product complies with EN 10223-1 standard

Applications

- ▶ Agriculture
- ▶ Motorway
- ▶ Industry




Life span 2x longer than EN 10244-2 heavily galvanised



Characteristics

Wire Ø (mm)	Length (m)	Number of barbs	Space between barbs (cm)	Weight (kg)	Rolls/pallet
1.7	100	4	10	5.1	96
1.7	250	4	10	12.7	64
1.7	500	4	10	25.4	36

Barb



ArcelorMittal Bissen & Bettembourg
 Route de Finsterthal, L-7703 Bissen
 T +352 835 772, F +352 835 698

www.arcelormittal.com/wiresolutions

