

Recommandations d'épissure

Recommandations CEN

Diamètre (D)	L=1200 D	a=60 D	b=180D
mm	m	m	m
9	10.8	0.54	1.62
12	14.4	0.72	2.16
14	16.8	0.84	2.52
16	19.2	0.96	2.88
18	21.6	1.08	3.24
20	24.0	1.20	3.60
22	26.4	1.32	3.96
24	28.8	1.44	4.32
26	31.2	1.56	4.68
28	33.6	1.68	5.04
30	36.0	1.80	5.40
32	38.4	1.92	5.76
33	39.6	1.98	5.94
34	40.8	2.04	6.12
35	42.0	2.10	6.30
36	43.2	2.16	6.48
37	44.4	2.22	6.66
38	45.6	2.28	6.84
39	46.8	2.34	7.02
40	48.0	2.40	7.20
41	49.2	2.46	7.38
42	50.4	2.52	7.56
43	51.6	2.58	7.74
44	52.8	2.64	7.92
45	54.0	2.70	8.10
46	55.2	2.76	8.28
47	56.4	2.82	8.46
48	57.6	2.88	8.64
49	58.8	2.94	8.82
50	60.0	3.00	9.00
51	61.2	3.06	9.18
52	62.4	3.12	9.36
53	63.6	3.18	9.54
54	64.8	3.24	9.72
55	66.0	3.30	9.90
56	67.2	3.36	10.08

