

Estate[®]WIRE 

Stronger. Longer lasting.

Fencing for Deer 




ArcelorMittal

EstateWIRE[®] FX

EstateWIRE[®] FX combines 2Life[®] anti-corrosive technology with the rigid, strength forming advantages of the FX knot to deliver a stronger, longer lasting deer fence.

We have been making longer lasting fencing for more than 30 years. Like our fencing products, we are here to stay.



GUARANTEED
2Life[®] anti-corrosive technology PLUS the rigid, strength forming FX knot deliver a strong and robust deer fence that will stand the test of time.



The advantages of EstateWIRE FX:

- Animal hide, skin and coat friendly, reducing the risk of injury to livestock and people
- Stronger than traditional hinge joint fence
- Better vertical rigidity due to solid vertical wires
- More horizontal rigidity, enabling an easier, more professional installation
- Manufactured to BS EN 10223-5
- Galvanised to BS EN 10244-2
- Guaranteed to last at least twice as long as zinc only galvanised products to BS EN 10244-2 Class A.

Rapid tying off

EstateWIRE FX is manufactured using continuous horizontal and vertical wires. The horizontal and vertical wires are held together at their cross over point by individual FX knots.

Removing the FX knots along a vertical wire allows the vertical wire to be removed quickly creating the horizontal tail wires for tying off.

Unlimited applications due to a comprehensive number of mesh apertures.



Bespoke specifications can be manufactured on request.

Our standard stock Estate[®]WIRE FX products:

228.6mm
228.6mm
177.8mm
177.8mm
177.8mm
177.8mm
152.4mm
152.4mm
127mm
127mm
101.6mm
76.2mm
76.2mm

FX13/190/7.5

Characteristics

- > Wire specification
2.50mm high tensile
- > Height
1905mm
- > Stay wire spacing
76.2mm
- > Length
50m
- > Nominal weight
80kg

228.6mm
228.6mm
177.8mm
177.8mm
177.8mm
177.8mm
152.4mm
152.4mm
127mm
127mm
101.6mm
76.2mm
152.4mm

FX13/190/15

Characteristics

- > Wire specification
2.50mm high tensile
- > Height
1905mm
- > Stay wire spacing
152.4mm
- > Length
100m
- > Nominal weight
105kg

228.6mm
228.6mm
177.8mm
177.8mm
177.8mm
177.8mm
152.4mm
152.4mm
127mm
127mm
101.6mm
76.2mm
228.6mm

FX13/190/22

Characteristics

- > Wire specification
2.50mm high tensile
- > Height
1905mm
- > Stay wire spacing
228.6mm
- > Length
100m
- > Nominal weight
86kg

203.2mm
203.2mm
203.2mm
177.8mm
177.8mm
177.8mm
152.4mm
152.4mm
152.4mm
127mm
127mm
152.4mm

FX12/180/15

Characteristics

- > Wire specification
2.50mm high tensile
- > Height
1854.2mm
- > Stay wire spacing
152.4mm
- > Length
100m
- > Nominal weight
99kg

101.6mm
101.6mm
101.6mm
101.6mm
101.6mm
101.6mm
101.6mm
101.6mm
101.6mm
101.6mm
101.6mm
101.6mm
101.6mm
101.6mm
101.6mm
101.6mm
101.6mm
101.6mm
101.6mm
101.6mm
50.8mm

FX19/180/5

Characteristics

- > Wire specification
2.50mm high tensile
- > Height
1828.8mm
- > Stay wire spacing
50.8mm
- > Length
50m
- > Nominal weight
125kg

Estate[®]WIRE 

Talk to an
Estate[®]WIRE
expert today:

fencingsales@arcelormittal.com

+44 (0)114 239 2601

Estate[®]WIRE FX is also suitable for infrastructure rail and road projects, and solar energy farms. Roll lengths available up to 500m for agriculture/highway/rail/infrastructure projects where specialist fencing installation equipment is used.

Full product replacement guarantee and details on how to register your product can be found at arcelormittal.com/estatewire/guarantee



MADE IN SHEFFIELD

Estate[®]WIRE 

Talk to an Estate[®]WIRE FX expert today:

Email: fencingsales@arcelormittal.com

Telephone: +44 (0)114 239 2601

Fax: +44 (0)114 264 2514

Follow us:



[arcelormittal.sheffield](https://www.facebook.com/arcelormittal.sheffield)



ArcelorMittal

ArcelorMittal Sheffield Ltd
Vulcan Works
Birley Vale Close
Sheffield
S12 2DB