

Estate[®]WIRE 

Stronger. Longer lasting.

Fencing for Horses and Foals 




ArcelorMittal

EstateWIRE[®] FX

EstateWIRE[®] FX combines 2Life[®] anti-corrosive technology with the rigid, strength forming advantages of the FX knot to deliver a stronger, longer lasting horse and foal fence.

We have been making longer lasting fencing for more than 30 years. Like our fencing products, we are here to stay.



GUARANTEED 2Life[®] anti-corrosive technology PLUS the rigid, strength forming FX knot deliver a strong and robust horse and foal fence that will stand the test of time.



The advantages of EstateWIRE FX:

- Animal hide, skin and coat friendly, reducing the risk of injury to livestock and people
- Stronger than traditional hinge joint fence
- Better vertical rigidity due to solid vertical wires
- More horizontal rigidity, enabling an easier, more professional installation
- Manufactured to BS EN 10223-5
- Galvanised to BS EN 10244-2
- Guaranteed to last at least twice as long as zinc only galvanised products to BS EN 10244-2 Class A.

Rapid tying off

EstateWIRE FX is manufactured using continuous horizontal and vertical wires. The horizontal and vertical wires are held together at their cross over point by individual FX knots.

Removing the FX knots along a vertical wire allows the vertical wire to be removed quickly creating the horizontal tail wires for tying off.

Unlimited applications due to a comprehensive number of mesh apertures.



ArcelorMittal


Bespoke specifications can be manufactured on request.

Our standard stock EstateWIRE FX products:

FX10/90/7.5

Characteristics

- ▶ Wire specification 2.50mm high tensile
- ▶ Height 914.4mm
- ▶ Stay wire spacing 76.2mm
- ▶ Length 50m
- ▶ Nominal weight 49kg




→ 76.2mm

FX12/110/5

Characteristics

- ▶ Wire specification 2.50mm high tensile
- ▶ Height 1117.6mm
- ▶ Stay wire spacing 50.8mm
- ▶ Length 50m
- ▶ Nominal weight 77kg




→ 50.8mm

FX12/110/7.5

Characteristics

- ▶ Wire specification 2.50mm high tensile
- ▶ Height 1117.6mm
- ▶ Stay wire spacing 76.2mm
- ▶ Length 50m/100m
- ▶ Nominal weight 59kg/118kg




→ 76.2mm

FX13/120/5

Characteristics

- ▶ Wire specification 2.50mm high tensile
- ▶ Height 1219.2mm
- ▶ Stay wire spacing 50.8mm
- ▶ Length 50m/100m
- ▶ Nominal weight 84kg/168kg




→ 50.8mm

FX13/120/7.5

Characteristics

- ▶ Wire specification 2.50mm high tensile
- ▶ Height 1219.2mm
- ▶ Stay wire spacing 76.2mm
- ▶ Length 50m/100m
- ▶ Nominal weight 64kg/128kg




→ 76.2mm

FX15/158/5

Characteristics

- ▶ Wire specification 2.50mm high tensile
- ▶ Height 1600.2mm
- ▶ Stay wire spacing 50.8mm
- ▶ Length 50m
- ▶ Nominal weight 103kg




→ 50.8mm

FX15/158/7.5

Characteristics

- ▶ Wire specification 2.50mm high tensile
- ▶ Height 1600.2mm
- ▶ Stay wire spacing 76.2mm
- ▶ Length 50m
- ▶ Nominal weight 78kg




→ 76.2mm

FX19/180/5

Characteristics

- ▶ Wire specification 2.50mm high tensile
- ▶ Height 1828.8mm
- ▶ Stay wire spacing 50.8mm
- ▶ Length 50m
- ▶ Nominal weight 125kg



→ 50.8mm

EstateWIRE FX is also suitable for infrastructure rail and road projects, and solar energy farms. Roll lengths available up to 500m for agriculture/highway/rail/infrastructure projects where specialist fencing installation equipment is used.

Full product replacement guarantee and details on how to register your product can be found at arcelormittal.com/estatewire/guarantee



MADE IN SHEFFIELD

Estate[®]WIRE 

Talk to an Estate[®]WIRE FX expert today:

Email: fencingsales@arcelormittal.com

Telephone: +44 (0)114 239 2601

Fax: +44 (0)114 264 2514

Follow us:



[arcelormittal.sheffield](https://www.facebook.com/arcelormittal.sheffield)



ArcelorMittal

ArcelorMittal Sheffield Ltd
Vulcan Works
Birley Vale Close
Sheffield
S12 2DB