



Rotation resistant hoist rope



24x7



24x17

24x7

24x17

Diameter		Section	Mass	Min. breaking load
mm	inch			
				2160 MPa
8	5/16	30,5	0,27	56
9	-	37,8	0,34	69
10	-	47,8	0,43	86
11	7/16	56,8	0,51	104
12	-	68,0	0,61	125
13	1/2	81,6	0,72	145
14	9/16	96,5	0,86	175
15	-	106,2	0,94	190
16	5/8	125,5	1,12	221
17	-	140,8	1,25	248
18	-	158,2	1,41	278
19	3/4	173,3	1,53	310
20	-	188,5	1,67	335
21	-	213,4	1,89	368
22	7/8	235,3	2,09	415
24	-	281,0	2,50	495
25,4	1	309,8	2,75	560
28	1-1/8	384,9	3,42	675
29	-	408,2	3,63	712
30	-	446,0	3,95	765
32	1-1/4	507,4	4,49	870
34	1-3/8	572,8	5,07	983
36	-	643,6	5,73	1095
38	1-1/2	717,1	6,38	1215
40	-	795,6	7,08	1345
42	-	877,2	7,81	1485
44	-	962,7	8,57	1630
82	-	3343,7	29,75	5652

Indicative values – Tolerance on diameter: ArcelorMittal design (0; +4%) – Mark for traceability on request



Depending on applications, design can be specifically adapted. Please contact us for further information.