

Surface lifts
Skilifte
Telesquíes


Débrayables
Detachable
Kuppelbar
Desembragables

Ame centrale textile ou compacte,
Câblage Lang préformé – Acier clair ou galvanisé.

Synthetic PP or solid plastic core,
Lang lay preformed – Bright or galvanized steel.

Faser- oder Plastikkompakteinlage,
Gleichschlag vorgeformt – Blank oder verzinkt.

Alma central textil o compacta,
Cableado Lang preformado – Acero claro o galvanizado.




6x7 Standard
6x(1+6)

6x7 Standard - Standard - Standard - Estándar

Diamètre Diameter Durchmesser Diámetro mm	Diamètre fils externes Wire diameter Draht Durchmesser Diámetros hilos externos kN	Masse Mass Gewicht Masa kg/m	Force de rupture minimale Minimum breaking load Mindestbruchkraft Fuerza de rotura mínima kN
9.50	1.00	0.300	54
12.00	1.30	0.505	92
14.00	1.50	0.675	123
16.00	1.70	0.865	162
18.00	1.90	1.075	215
19.50	2.10	1.307	240

Valeurs indicatives – Approximate values – Richtwerte – Valores indicativos
To convert rope MBL in kN to tons (2000 lbs) multiply by 0.1124



6x7 Compacté
6x(1+6)

6x7 Compacté - Compacted - Kompakt - Compacto

Diamètre Diameter Durchmesser Diámetro mm	Diamètre fils externes Wire diameter Draht Durchmesser Diámetros hilos externos kN	Masse Mass Gewicht Masa kg/m	Force de rupture minimale Minimum breaking load Mindestbruchkraft Fuerza de rotura mínima kN
12.00	1.35	0.550	101
14.00	1.57	0.745	128
16.00	1.80	0.980	172
18.00	2.00	1.210	230
19.50	2.20	1.470	260

Valeurs indicatives – Approximate values – Richtwerte – Valores indicativos
To convert rope MBL in kN to tons (2000 lbs) multiply by 0.1124

Nous consulter pour plus d'informations.
Please contact us for further information.
Kontaktieren Sie uns für weitere Informationen.
Para más información, consúltenos.

